

# Questionnaire Dry Grinding

Customer Data				
Company name			Responsible person	
Street, Street No.			Position	
Postal code, City			E-Mail	
Country			Telephone number	
VAT (if EU customer)			Mobile phone	
Ambient conditions				
Installation location or country			Ambient temperature max.	°C
Altitude above sea level (m)			Ambient temperature min.	°C
Choose your application				
<input type="checkbox"/> Fishfeed			<input type="checkbox"/> Compound Feed	
<input type="checkbox"/> Alternative fuel			<input type="checkbox"/> Food	
<input type="checkbox"/> Breweries & Distilleries			<input type="checkbox"/> Wood	
<input type="checkbox"/> Grain			<input type="checkbox"/> Petfood	
<input type="checkbox"/> Chemicals			<input type="checkbox"/> Other:	
Application				
Grinding material			Particle size after grinding	
Composition			% smaller than	mm
Bulk density feed product (t/m <sup>3</sup> )			% smaller than	mm
Moisture (%)			% smaller than	mm
Fat content (%)			% smaller than	mm
Max. particle size (mm)			% smaller than	mm
Capacity (t/h)			or screen size (mm)	
Operation	<input type="checkbox"/> continuous		<input type="checkbox"/> batch operation	
Technical Conditions				
Power supply (V)			Explosion protection	<input type="checkbox"/> yes <input type="checkbox"/> no
Frequency	<input type="checkbox"/> 50 Hz	<input type="checkbox"/> 60 Hz	If yes, ATEX inside zone <input type="checkbox"/> 20 <input type="checkbox"/> 21 <input type="checkbox"/> 22	
Control voltage	<input type="checkbox"/> 24 V DC	<input type="checkbox"/> 110 V AC	ATEX outside zone <input type="checkbox"/> 20 <input type="checkbox"/> 21 <input type="checkbox"/> 22	
			Other standards	
Comments				